

Stonesoft Next Generation Firewall

Release Notes

5.10.7

Revision A

Table of contents

1 About this release	
System requirements	-
1 About this release	6
Compatibility	7
2 New features	:
2 110W 10000100	
3 Enhancements	9
4 Resolved issues	10
5 Installation instructions	1
5 Installation instructions	11
6 Known issues	12
6 Known issues	12
7 Find product documentation	13
Product documentation	

About this release

This document contains important information about this release of Stonesoft® Next Generation Firewall by Forcepoint (Stonesoft NGFW; formerly known as McAfee® Next Generation Firewall). We strongly recommend that you read the entire document.

NGFW version 5.10.1 has been evaluated against the Common Criteria Network Devices Protection Profile with Extended Package Stateful Traffic Filter Firewall. For more details, see https://www.niap-ccevs.org/Product/ Compliant.cfm?pid=10669.



Note: We have started rebranding the NGFW product and the NGFW product documentation. We use Stonesoft in the product name in this document. However, the old product name is still used in the NGFW appliances, the NGFW engine software, and the product documentation set that we created for the NGFW 5.10.0 release.

System requirements

Make sure that you meet these basic hardware and software requirements.

Stonesoft NGFW appliances

We strongly recommend using a pre-installed Stonesoft NGFW appliance as the hardware solution for new Stonesoft NGFW installations.



Note: Some features in this release are not available for all appliance models. See Knowledge Base article 10192 and Knowledge Base article 9743 for up-to-date appliance-specific software compatibility information.

Appliance model	Supported roles	Image type
FW-315	Firewall/VPN	x86-64-small
320X (MIL-320)	Firewall/VPN	x86-64
IPS-1205	IPS and Layer 2 Firewall	x86-64
FWL321	Firewall/VPN	x86-64-small
NGF321	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
FWL325	Firewall/VPN	x86-64-small
NGF325	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
110	Firewall/VPN	x86-64-small
1035	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
1065	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
1301	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
1302	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
1401	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
1402	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64

Appliance model	Supported roles	Image type
3201	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
3202	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
3205	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
3206	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
3207	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
3301	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
3305	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
5201	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
5205	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64
5206	Firewall/VPN, IPS, and Layer 2 Firewall	x86-64

Sidewinder S-series appliances

These Sidewinder appliances can be re-imaged to run Stonesoft NGFW software.

Appliance model	Supported roles	Image type
S-1104	Firewall/VPN	x86-64
S-2008	Firewall/VPN	x86-64
S-3008	Firewall/VPN	x86-64
S-4016	Firewall/VPN	x86-64
S-5032	Firewall/VPN	x86-64
S-6032	Firewall/VPN	x86-64

Certified Intel platforms

We have certified specific Intel-based platforms for Stonesoft NGFW.

The tested platforms can be found at https://support.forcepoint.com under the Stonesoft Next Generation Firewall product.

We strongly recommend using certified hardware or a pre-installed Stonesoft NGFW appliance as the hardware solution for new Stonesoft NGFW installations. If it is not possible to use a certified platform, Stonesoft NGFW can also run on standard Intel-based hardware that fulfills the hardware requirements.

Basic hardware requirements

You can install Stonesoft NGFW on standard hardware with these basic requirements.

(Recommended for new deployments) Intel® Xeon®-based hardware from the E5-16xx product family or higher



Note: Legacy deployments with Intel[®] Core[™]2 are supported.

IDE hard disk and CD drive



Note: IDE RAID controllers are not supported.

- Memory:
 - 4 GB RAM minimum for x86-64-small installation
 - 8 GB RAM minimum for x86-64 installation
- VGA-compatible display and keyboard
- One or more certified network interfaces for the Firewall/VPN role
- Two or more certified network interfaces for IPS with IDS configuration
- Three or more certified network interfaces for Inline IPS or Layer 2 Firewall

For information about certified network interfaces, see Knowledge Base article 9721.

Master Engine requirements

Master Engines have specific hardware requirements.

- Each Master Engine must run on a separate physical device. For more details, see the Stonesoft Next Generation Firewall Installation Guide.
- All Virtual Security Engines hosted by a Master Engine or Master Engine cluster must have the same role and the same Failure Mode (fail-open or fail-close).
- Master Engines can allocate VLANs or interfaces to Virtual Security Engines. If the Failure Mode of the Virtual IPS engines or Virtual Layer 2 Firewalls is Normal (fail-close) and you want to allocate VLANs to several engines, you must use the Master Engine cluster in standby mode.
- Cabling requirements for Master Engine clusters that host Virtual IPS engines or Layer 2 Firewalls:
 - Failure Mode Bypass (fail-open) requires IPS serial cluster cabling.
 - Failure Mode Normal (fail-close) requires Layer 2 Firewall cluster cabling.

For more information about cabling, see the Stonesoft Next Generation Firewall Installation Guide.

Virtual appliance node requirements

You can install Stonesoft NGFW on virtual appliances with these hardware requirements. Also be aware of some limitations.

(Recommended for new deployments) Intel® Xeon®-based hardware from the E5-16xx product family or higher



Note: Legacy deployments with Intel[®] Core[™]2 are supported.

- One of the following hypervisors:
 - VMware ESXi 5.5 and 6.0



Note: Stonesoft Next Generation Firewall 5.10.7 does not support integration with Intel Security Controller and deployment on VMware NSX.

- KVM (KVM is tested as shipped with Red Hat Enterprise Linux Server 7.0)
- Oracle VM server 3.3 (tested with Oracle VM server 3.3.1)
- 8 GB virtual disk
- 4 GB RAM minimum
- A minimum of one virtual network interface for the Firewall/VPN role, three for IPS or Layer 2 Firewall roles

When Stonesoft NGFW is run as a virtual appliance node in the Firewall/VPN role, these limitations apply:

· Only Packet Dispatching CVI mode is supported.

- Only standby clustering mode is supported.
- Heartbeat requires a dedicated non-VLAN-tagged interface.

When Stonesoft NGFW is run as a virtual appliance node in the IPS or Layer 2 Firewall role, clustering is not supported.

Build version

Stonesoft Next Generation Firewall 5.10.7 build version is 14096.

Product binary checksums

Use the checksums to make sure that the installation files downloaded correctly.

sg engine 5.10.7.14096 x86-64.iso

```
SHA1SUM:
1e95d3ad15af0ebc2da9b751300d6424b019fb15
SHA256SUM:
69b774fbcd016cf5ca5749c6490786a71c0177bf5efbfa2b65ba0b67af4dac5c
SHA512SUM:
b33652cd03d684082f170e917541c4e8
327a7758f8538270ae6da3e3b20e72e5
dbe3589da669ab38d962755e356c2a3c
472c9d02f2656ae13972f2c1ac30ecef
```

sg_engine_5.10.7.14096_x86-64.zip

```
SHA1SUM:
60f046302e5f36da21eae209131075e6351f5c49
SHA256SUM:
8b07bf6c52a5580206b74d4d83cbed98465e73986eab522cfec4a2bfdf22c9f1
SHA512SUM:
ad050e3ae07e9bb0c1d0e5d1d02e25b2
0daa49bcd5b5aab909d98a850950c09c
2a2cee5c4e33b30de62d4b8e74c77285
a53b878f8c6e0acae69f107f87d0467f
```

sg engine 5.10.7.14096 x86-64-small.iso

```
SHA1SUM:
bae84154741c710021e33febcb84515ef3434d98
47a2a372e6e247405b2085d707d3c54ff824ee3b85d022e6852f37091efbebae
SHA512SUM:
b6b0fab8d6d711df61cc12a85eae4ba8
cc721cb3e55e5fe5c0c87f9ce3274f35
b13eda30a3bc81b35b281e4bdf7d7a81
1ddb3694a657acf748ae8f8f2d33c6b6
```

sg_engine_5.10.7.14096_x86-64-small.zip

```
SHA1SUM:
9ab176c0b172704decb6271a239e7ab8b96486b2
c9736ee8250d722fd3410bd9d7390b984ecc46ef4ecf26868da2ca754b7ae03d
cebaea4aa2d2742088133f902d01a9a5
1ef6bc527b535ad3be2cb55f17524048
375f3df954ad650baf60519ccce56d13
f3fc13bf92d1115e692dfea9b3e9d024
```

Compatibility

Stonesoft NGFW 5.10.7 is compatible with the following component versions.

- McAfee® Security Management Center (SMC) 5.10.0 or later
- Dynamic Update 703 or later
- Stonesoft IPsec VPN Client 5.3.0 or later
- McAfee® VPN Client for Windows 5.9.0 or later
- McAfee® VPN Client for Mac OS X 1.0.0 or later
- McAfee® VPN Client for Android 1.0.1 or later
- · Server Pool Monitoring Agent 4.0.0 or later
- McAfee® Logon Collector 2.2 and 3.0
- McAfee® Advanced Threat Defense 3.6
- McAfee® Endpoint Intelligence Agent (McAfee EIA) 2.5

New features

This release of the product includes these new features.



Note: Stonesoft Next Generation Firewall 5.10.7 does not support integration with Intel Security Controller and deployment on VMware NSX.

Support for Threat Intelligence Exchange

Stonesoft NGFW can now query file reputations and receive reputation updates from the McAfee® Threat Intelligence Exchange (TIE) server. TIE makes it possible for administrators to tailor comprehensive local threat intelligence from global intelligence data sources, such as McAfee® Global Threat Intelligence™ (McAfee GTI), endpoints, gateways, and other security components. File reputation data is exchanged using the McAfee® Data Exchange Layer (DXL) broker network. File reputation updates ensure that Stonesoft NGFW engines always have the latest file reputations available for use in file filtering.

Single sign-on (SSO) to SSL VPN Portal

The SSL VPN Portal (reverse web proxy) can be configured to cache user credentials. The portal logs on to the back-end servers with the credentials as if they came from the web browser at the endpoint. You can group the servers that use the same credentials by SSO domain, to further reduce the need to re-enter the password.

New tunnel type for the route-based VPN

A new tunnel type for the route-based VPN allows the use of tunnel mode IPsec without an additional tunneling layer. The route-based VPN configuration dialog box has been improved.

Connectivity between Stonesoft NGFW and SMC using IPv6

Engines that only use IPv6 to connect to the Internet can now be managed by SMC over the Internet using IPv6based management connections. Connectivity between SMC components still requires IPv4 addressing and connectivity.

Network Security for Industrial Control Systems (ICS)

ICS support has been enhanced with deep inspection support for DNP3 (TCP/UDP) and Open Platform Communications Unified Architecture (OPC UA).

Safe search support

Stonesoft NGFW can be configured to enforce safe search usage for Google, Bing, Yahoo, and DuckDuckGo web searches.

Enhancements

This release of the product includes these enhancements.

Enhancements in Stonesoft NGFW version 5.10

Enhancement	Description
Advanced Threat Defense communication logging improvements	Improvements have been made to the communication protocol and logging features between McAfee® Advanced Threat Defense and Stonesoft NGFW. Stonesoft NGFW now logs the dynamic analysis results when available from Advanced Threat Defense. Stonesoft NGFW provides the file name, destination IP address, and URL details when sending the file to Advanced Threat Defense for analysis.
File filtering improvements	Improvements have been made to file type detection and filtering. We recommend that you update your file filtering policies with the new file type categories.
DHCP services	It is now possible to use DHCP server and DHCP relay services on different interfaces of the same Stonesoft NGFW engine.

Enhancements in Stonesoft NGFW version 5.10.3

Enhancement	Description
Dynamic routing enhancements	Dynamic routing features, such as graceful restart for OSPF and BGP, have been improved. The stability of dynamic routing has also been improved.

Enhancements in Stonesoft NGFW version 5.10.4

Enhancement	Description
Improved alerting for offline transitions	Alerting for offline transitions has been improved. Alerts are now created for unexpected offline transitions, such as heartbeat recovery, or nodes that have different policies.
Faster policy installation for Virtual Security Engines	Policy installation is now faster in environments that have many Virtual Security Engines.

Resolved issues

These issues are resolved in this release of the product. For a list of issues fixed in earlier releases, see the Release Notes for the specific release.

Description	Role	Issue number
Network traffic processing might stop on 1400 Series appliances if the interface modules MOD-EM2-10G-SFP-4/MOE10F4 or MOD-40G-2/MO40F2 are in use.	FW	133650
modules MOD-EM2-10G-SFP-4/MOE10F4 of MOD-40G-2/MO40F2 are in use.	IPS	
	L2FW	
The dynamic routing process might not start automatically after restarting the Security Engine if the configuration was done in the Management Client.	FW	134502

Installation instructions

Use these high-level steps to install SMC and the Stonesoft NGFW engines.

For detailed information, see the Stonesoft Next Generation Firewall Installation Guide. All guides are available for download at https://support.forcepoint.com.



Note: The sgadmin user is reserved for SMC use on Linux, so it must not exist before SMC is installed for the first time.

- 1. Install the Management Server, the Log Servers, and optionally the Web Portal Servers.
- Import the licenses for all components.
 - You can generate licenses at https://stonesoftlicenses.forcepoint.com/.
- 3. Configure the Firewall, IPS, or Layer 2 Firewall elements with the Management Client using the Security **Engine Configuration view.**
- 4. To generate initial configurations for the engines, right-click each Firewall, IPS, or Layer 2 Firewall element, then select Configuration > Save Initial Configuration.
 - Make a note of the one-time password.
- 5. Make the initial connection from the engines to the Management Server, then enter the one-time password.
- 6. Create and upload a policy on the engines using the Management Client.

Upgrade instructions

Take the following into consideration before upgrading licenses, engines, and clusters.

- Upgrading to version 5.10.x is only supported from version 5.8.x or later. If you have an earlier version, first upgrade to the latest 5.8.x version.
- Stonesoft NGFW 5.10.x requires an updated license if upgrading from version 5.9.x or earlier. The license upgrade can be requested at https://stonesoftlicenses.forcepoint.com/. Install the new license using the Management Client before upgrading the software. If communication between the SMC and the license server is enabled and the maintenance contract is valid, the license is updated automatically.
- To upgrade the engine, use the remote upgrade feature or reboot from the installation CD and follow the instructions. For detailed instructions, see the Stonesoft Next Generation Firewall Installation Guide.

Take the following software architecture information into consideration.

- Stonesoft NGFW appliances support only the software architecture version with which they come installed. 32-bit versions (i386) can only be upgraded to another 32-bit version and 64-bit versions (x86-64) can only be upgraded to another 64-bit version.
- Clusters can only have online nodes that use the same software architecture version.
- State synchronization between 32-bit and 64-bit versions is not supported.
- Changing the architecture of third-party servers using software licenses requires the software to be fully reinstalled from CD.
- Stonesoft NGFW version 5.10 only supports 64-bit software architecture. Except for the FW-315 appliance, the last supported software version for 32-bit Firewall/VPN appliances is 5.8.
- To upgrade a cluster (consisting of FW-315 appliances or third-party hardware using software licenses) from a 32-bit to 64-bit version, see the following Knowledge Base article: 81935.

Known issues

For a list of known issues in this product release, see Knowledge Base article 10138.

Known limitations

This release of the product includes these known limitations.

Limitation	Description
Inspection in asymmetrically routed networks	In asymmetrically routed networks, using the stream- modifying features (TLS Inspection, URL filtering, and file filtering) can make connections stall.
SSL/TLS inspection in capture (IDS) mode	Due to SSL/TLS protocol security features, SSL/ TLS decryption in capture (IDS) mode can only be applied in a server protection scenario when RSA key exchange negotiation is used between the client and the server.
Inline Interface disconnect mode in the IPS role	The disconnect mode for Inline Interfaces is not supported on IPS virtual appliances, IPS software installations, IPS appliance models other than IPS-6xxx, or modular appliance models that have bypass interface modules.

Find product documentation

On the Forcepoint support website, you can find information about a released product, including product documentation, technical articles, and more.

You can get additional information and support for your product on the Forcepoint support website at https:// support.forcepoint.com. There, you can access product documentation, Knowledge Base articles, downloads, cases, and contact information.

Product documentation

Every Forcepoint product has a comprehensive set of documentation.

- Stonesoft Next Generation Firewall Product Guide
- Stonesoft Next Generation Firewall online Help



Note: By default, the online Help is used from the Forcepoint help server. If you want to use the online Help from a local machine (for example, an intranet server or your own computer), see Knowledge Base article 10097.

Stonesoft Next Generation Firewall Installation Guide

Other available documents include:

- Stonesoft Management Center Appliance Hardware Guide
- Stonesoft Next Generation Firewall Hardware Guide for your model
- Stonesoft SMC API Reference Guide
- Stonesoft VPN Client User Guide for Windows or Mac
- Stonesoft VPN Client Product Guide

The following documents included in appliance deliveries still use the old product name and brand:

- McAfee Security Management Center Appliance Quick Start Guide
- McAfee Next Generation Firewall Quick Start Guide

Copyright © 1996 - 2016 Forcepoint LLC Forcepoint™ is a trademark of Forcepoint LLC. SureView®, ThreatSeeker®, TRITON®, Sidewinder® and Stonesoft® are registered trademarks of Forcepoint LLC. Raytheon is a registered trademark of Raytheon Company. All other trademarks and registered trademarks are property of their respective owners.